


Jan.1.2026 Copyright 2026 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
 In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.



Recommended land pattern dimension of PCB





HRS DRAWING FOR REFERENCE

- Notes
- 1 SMT lead - coplanarity : 0.1 max.
 - 2 This product has no polarity to pattern for mounting.
 - 3 Emboss carrier tape package is applied on this product. Please refer to the sheet 2/2 for the details.

2	Phosphor blonze	Contact area : Gold 0.1 μ m min	5	Polyester	(Top cover tape)		
		Lead : Gold 0.05 μ m min		Polyethylene	(Emboss carrier tape)		
1	LCP	Under plating : Nickel 1 μ m min	3	Phosphor blonze	Tin - plating		
		Beige UL94V-0					
NO.	MATERIAL	FINISH . REMARKS	NO.	MATERIAL	FINISH . REMARKS		
UNITS mm		SCALE 4 : 1	COUNT 1	DESCRIPTION OF REVISIONS DIS-F-00011032	DESIGNED MT. ITANO	CHECKED HT. YAMAGUCHI	DATE 20211007
HRS HIROSE ELECTRIC CO., LTD.		APPROVED : KJ. KATAYOSE	20050105	DRAWING NO. EDC3-151989-01			
		CHECKED : HS. OKAWA	20050105	PART NO. FX10B-120S-SV(21)			
		DESIGNED : KT. DOI	20050105	CODE NO. CL0570-0252-5-21			
		DRAWN : KT. DOI	20050105				

Jan.1.2026 Copyright 2026 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
 In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

Drawing for packing (2:1)



- Notes
- 4 1 reel : 1,000 connectors.
 - 5 Minimum 10 compartments from both reel ends remain empty.
 - 6 This product has no polarity to tape and reel packaging.
 - 7 The dimensions in parentheses are for reference.

HRS	DRAWING NO.	EDC3-151989-01	
	PART NO.	FX10B-120S-SV(21)	
	CODE NO.	CL0570-0252-5-21	